

Amendments to the Claims:

This listing of claims 1-13 will replace all prior versions and listings of claims in the application.

Listing of the Claims:

1. (currently amended) A toy vehicle comprising:

a hinged, three part chassis having a first longitudinal end and a second, opposing longitudinal end and including a central chassis portion having opposing first and second lateral sides, a first lateral chassis portion pivotally coupled with the central chassis portion on the first lateral side of the central chassis portion, and a second lateral chassis portion pivotally coupled to the central chassis portion on a second lateral side of the central chassis portion, wherein the first and second lateral chassis portions are coupled so as to pivot with respect to the central chassis portion in a common plane;

a plurality of road wheels rotatably supported from the first chassis portion, at least a first road wheel of the plurality being located proximal the first end of the first chassis portion and at least a second road wheel of the plurality being located proximal the second end of the first chassis portion; and

another plurality of road wheels rotatably supported from the second chassis portion.

2. (original) The toy vehicle according to claim 1 wherein each of the first and second lateral chassis portions is pivotally coupled directly with the central chassis portion at the second longitudinal end of the vehicle.

3. (currently amended) A ~~The toy vehicle of claim 2 further~~ comprising:

a hinged, three part chassis having a first longitudinal end and a second, opposing longitudinal end and including a central chassis portion having opposing first and second lateral sides, a first lateral chassis portion pivotally coupled with the central chassis portion on the first lateral side of the central chassis portion, and a second lateral chassis portion pivotally coupled to

the central chassis portion on a second lateral side of the central chassis portion, wherein the first and second lateral chassis portions are coupled so as to pivot with respect to the central chassis portion in a common plane, wherein each of the first and second lateral chassis portions is pivotally coupled directly with the central chassis portion at the second longitudinal end of the vehicle;

a plurality of road wheels rotatably supported from the first chassis portion;

another plurality of road wheels rotatably supported from the second chassis portion;

and

a pair of links, each link being pivotally coupled to the central chassis portion and to a separate one of the first and second lateral chassis portions at the first longitudinal end of the vehicle so as to permit the first longitudinal end of each lateral chassis portion to pivot away from and towards the central chassis portion.

4. (original) The toy vehicle according to claim 3 further comprising a separate light source in each link.

5. (original) The toy vehicle according to claim 3 further comprising at least one spring member positioned to bias at least one of the first and second lateral chassis portions against the central chassis portion.

6. (original) The toy vehicle of claim 5 further comprising an electric power supply located at the second longitudinal end of the vehicle.

7. (original) The toy vehicle according to claim 1 further comprising an electric power supply mounted to the central chassis portion at the second longitudinal end of the vehicle.

8. (currently amended) ~~The A~~ toy vehicle according to claim 1 further comprising:

a hinged, three part chassis having a first longitudinal end and a second, opposing longitudinal end and including a central chassis portion having opposing first and second lateral sides, a first lateral chassis portion pivotally coupled with the central chassis portion on the first lateral side of the central chassis portion, and a second lateral chassis portion pivotally coupled to the central chassis portion on a second lateral side of the central chassis portion, wherein the first and second lateral chassis portions are coupled so as to pivot with respect to the central chassis portion in a common plane;

a plurality of road wheels rotatably supported from the first chassis portion;

another plurality of road wheels rotatably supported from the second chassis portion; and

a plurality of strips removably attached to an outer circumferential tread surface of at least one road wheel on each of the first and second lateral chassis portions.

9. (original) The toy vehicle according to claim 8 wherein each road wheel includes a resiliently flexible tire and wherein each strip is formed of a material having a lower coefficient of friction than a material forming the tire receiving the strip.

10. (original) The toy vehicle of claim 9 wherein the strips define a non-zero angle with an axis of rotation of the at least one road wheel.

11. (currently amended) ~~The A~~ toy vehicle ~~according to claim 1~~ comprising:

a hinged, three part chassis having a first longitudinal end and a second, opposing longitudinal end and including a central chassis portion having opposing first and second lateral sides, a first lateral chassis portion pivotally coupled with the central chassis portion on the first lateral side of the central chassis portion, and a second lateral chassis portion pivotally coupled to the central chassis portion on a second lateral side of the central chassis portion, wherein the first and second lateral chassis portions are coupled so as to pivot with respect to the central chassis portion in a common plane; a plurality of road wheels rotatably supported from the first chassis

portion; and another plurality of road wheels rotatably supported from the second chassis portion; and

wherein each of the first and second lateral chassis portions includes an electric motor drivingly coupled with at least one of the plurality of road wheels rotatably supported on the lateral chassis portion.

12. (original) The toy vehicle of claim 11 wherein each electric motor is reversible and is drivingly coupled with at least a pair of the road wheels rotatably on the lateral chassis portion including the motor.

13. (currently amended) ~~The A~~ toy vehicle of ~~claim 1~~ further comprising:

a hinged, three part chassis having a first longitudinal end and a second, opposing longitudinal end and including a central chassis portion having opposing first and second lateral sides, a first lateral chassis portion pivotally coupled with the central chassis portion on the first lateral side of the central chassis portion, and a second lateral chassis portion pivotally coupled to the central chassis portion on a second lateral side of the central chassis portion, wherein the first and second lateral chassis portions are coupled so as to pivot with respect to the central chassis portion in a common plane;

a plurality of road wheels rotatably supported from the first chassis portion;

another plurality of road wheels rotatably supported from the second chassis portion; and

first and second major opposing outer sides, wherein the pluralities of road wheels are of a size with respect to a remainder of the vehicle such that at least four of the pluralities of wheels can contact and support either of the first and second major outer sides of the vehicle on a planar support surface with either of the first and second major outer sides facing the planar support surface.